

# FONDO TOWN

## SCHEDA TECNICA

Revisione : 16/02/2022

Prodotto: **Fondo Town**

Categoria: Fondi

Azienda: Loggia

### General Characteristics

Plastic coating based on acrylic resins in emulsion, silica fillers and fine grain size and inorganic pigments with high durability.

### Application

Fondo Town is a colorable primer to be used as a base coat for KEYTOWN on prepared walls

### Preparation



New External Surfaces: Make sure that the surface is perfectly dry and cured - not less than 4 weeks for civil plasters and 2 weeks for premixed plasters. If necessary, level any imperfections with FLYSTUK.



In case of very chalking substrates it is advisable to replace FISSACRIL with the solvent-based insulation ISOL 45.



### Application Methods



American spatula: Spread the product as it is with a smooth American spatula letting the thickness of the grain guide you, distributing it evenly.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	2 ÷ 4	µm per coat
Dust dry:	1	h
Repaintable after:	6-8	h

Deep dry:	48	h
Tool cleaning:	water	

## Painting:



The product can be colored with the tinting systems of MAXXI and L'ANGELO OX lines.

## Technical features:

Specific weight:	1,85 ÷ 2	Kg/l
Viscosity:	30.000 ÷ 40.000	cPs
pH:	7-8	
Solid in weight:	81%	
Theoretical yield:	1-1.5	mq/l
Granulometry:	0.2-0.7	
Color:	Bianco e Colori di Cartella	
Appearance:	Opaco	
Packs	5 - 25	

## Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**