

LAVABILE ECO

SCHEDA TECNICA

Revisione : 25/08/2023

Prodotto: **Lavabile ECO**

Categoria: Idropitture per Interni

Azienda: Loggia

General Characteristics

Velvety breathable water-based paint, formulated with special emulsions; it is environmentally friendly as the paint is free from glycols, formaldehyde and coalescents. Scented and anti-drip. It has a high whiteness, a high hiding power and excellent resistance to washing.

Application

Suitable for painting all internal wall surfaces. Applicable on plasters based on hydraulic binders, gypsum or plasterboard, and absorbent conglomerates of various kind, both new and old provided they do not crumble.

Preparation of the surface



New internal surfaces: Make sure that the substrate is perfectly dry and seasoned - no less than 4 weeks for civil plasters and 2 weeks for premixed plasters. If necessary fill any holes or imperfections with FLYSTUK and sand, clean the surfaces and then apply a coat of ISOLANTE ECO. After 4-6 hours paint with two coats of LAVABILE ECO following the technical indications below.



Internal Painted Surfaces: Eliminate any trace of mold by brushing off the efflorescences after having treated them with acid, sanitize with a coat of MUFFACID. Remove flaky residues of old paint and, if necessary, fill and smooth imperfections with FLYSTUK; sand and clean the surfaces. Then apply a coat of ISOLANTE ECO and after 4-6 hours paint with two coats of LAVABILE ECO following the technical indications below.



Application Methods



Brush: Dilute 25-30% with water for both the first and second coat. Wait 5-6 hours between one application and the next.



Roller: Dilute 20% with water for both the first and second coat. Wait 5-6 hours between one application and the next.



Airless: In airless applications the dilution varies depending on the equipment and pressure used.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	35 ÷ 50	µm per coat
Dust dry:	0,5	h
Repaintable after:	5 ÷ 6	h
Deep dry:	24	h
Tool cleaning:	water	

Painting:



The product can be colored with the L'ANGELO and L'ANGELO OX tinting system or with the universal dyes available on the market.

It is advisable to mix different manufacturing batches of the same color together to avoid possible differences in tone during application.

Specific weight:	1,58 ÷ 1,63	Kg/l
Viscosity:	12.000 ÷ 16.000	cPs
pH:	7	
Solid in weight:	65%	
Theoretical yield:	10 – 12	mq/l
Washability	>5000	Brush strokes
Color:	White and Card Colors	
Appearance:	Velvety satin	
Packaging:	4 - 14	l

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.