

# RAIN PROTEX

## SCHEDA TECNICA

Revisione : 31/08/2023

Prodotto: **Rain Protex**

Categoria: Isolanti Fissativi

Azienda: Loggia

### General Characteristics

Colorless siloxane water repellent for exteriors and interiors with excellent resistance to alkanes. It can be used as a colorless non-film-forming finish for concrete, mineral plasters, fiber cement panels, silico-limestone or brick masonry, mineral-based natural and artificial stone and wall paints.

### Use

Suitable for the decoration of interior elements of classic or modern high-prestige buildings.

### Media Preparation



The product must be used as it is on very crumbling surfaces or where a high quality penetration is desired. Eliminate from the surface any cracks which have a width greater than 0.3 mm.



Thoroughly clean the surface which must be free of traces of oil or grease or debris of various kinds. If a high-pressure cleaner is used to clean the surfaces, wait until all the water has evaporated before applying the product. Apply the product until a clear rejection of the surface.



### Application Methods



Brush or spray: ready to use. For spray application, use low pressure.

Application temperature:	+10÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	80-120	µm per coat
Dust dry:	2-4	h
Repaintable after:	2-4	h
Deep dry:	24	h
Tool cleaning:	with water	

The product, if applied in closed environments, requires a continuous exchange of air. Apply the product on a thoroughly clean surface. The yield may vary according to the characteristics of the support. Do not apply the product in direct sunlight.

Specific weight:	0,95 ÷ 1,05	Kg/l
Viscosity:	2000-300	cPs
pH:	7-8	
Solid in weight:	3%	
Theoretical yield:	0,1 a 3 l/mq per mano a seconda delle capacità di assorbimento del supporto.	mq/l
Color	without color	
Appearance	milky	
Packaging:	1 - 5 - 10	l

## **Storage:**

---



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## **Safety Precautions:**

---

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## **Warnings**

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**

