

# MUFFA CID

## SCHEDA TECNICA

Revisione : 09/10/2023

Prodotto: **Muffa Cid**  
Categoria: Isolanti Fissativi  
Azienda: Loggia

**General Characteristics** Transparent colorless water-based product with the addition of special broad-spectrum anti-fungal and bacterial agents.

### Use

Recommended for the treatment of all masonry surfaces (rough and painted plaster, exposed concrete, plasterboard, etc.) which are infested with mould. Useful in rooms with a high level of humidity, with walls facing north, or in rooms where condensation is easy to form.

### Support preparation

New and Painted Surfaces, both Internal and External: Eliminate any traces of mold by brushing away the efflorescence after treating them with acid. Then sanitize with a coat of MUFFACID.

### Application Methods



Brush/roller: ready to use

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	non applicabile	µm per coat
Dust dry:	0,5	h
Repaintable after:		h
Deep dry:	12	h
Tool cleaning:	water	

Specific weight:	1	Kg/l
Viscosity:		cPs
pH:	7-8	
Solid in weight:		
Theoretical yield:	14-16	mq/l
Recommended coats of paint:	Colorless	
Color:	Transparent	
Appearance:	1 - 5	I

## **Storage:**

---



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## **Safety Precautions:**

---

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## **Warnings**

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**