

# MICROUNIFORM

## SCHEDA TECNICA

Revisione : 02/03/2026

Prodotto: **Microuniform**

Categoria: Microloggia

Azienda: Loggia

### General Characteristics

MICROUNIFORM is a resinous primer for the MICROLOGGIA levelling cycle and as a contact promoter.

#### Use

MICROUNIFORM is suitable as an anchoring primer on cementitious substrates, both indoors and outdoors, and as a levelling agent before applying the MICROVETRO BI finish. It reduces and evens out the absorption of substrates.

### Preparation



Ensure that the self-levelling floor or walls are completely dry.



### Application Methods



Roller or brush: READY TO USE

Apply MICROUNIFORM and after approximately 2-3 hours apply MICROPRIMER ATTAC.

MICROLOGGIA cycle finish:

Wait 48-72 hours after applying the second coat of MICROLOGGIA 3, apply one coat of MICROUNIFORM and after about 2-4 hours apply MICROVETRO BI glossy or matt.

Application temperature:	+5 +40	°C
Relative humidity of application:	< 50%	
Recommended thickness:	a few millimetres	µm per coat
Repaintable after:	2-4	h
Tool cleaning:	water	
Specific weight:	1,00	Kg/l
pH:	7 – 8	
Theoretical yield:	14	mq/l
Packaging:	1 - 5	kg

## **Storage:**

---



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## **Safety Precautions:**

---

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## **Warnings**

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**