

MICROSUPER 7

SCHEDA TECNICA

Revisione : 17/02/2023

Prodotto: **Microsuper 7**

Categoria: Microloggia

Azienda: Example

General Characteristics

Powder filler for Microloggia cycle with excellent adherence and workability. Excellent thixotropy which avoids sagging. Ease of application. High resistance and excellent sandability.

Application

Filler used to mask the joints of tile floors, porcelain stoneware, etc. for internal and external use to obtain a smooth surface as preparation of the subsequent MICROPRIMER ATTAC in the Microloggia cycle.

Media Preparation



If present dirt, oil or non-stick product stains, act on the surface mechanically or with specific detergents.



Apply 2-3 coats of MICROSUPER7 in order to obtain a total coverage of the joints.



Furthermore, on critical floors and/or with traces for systems, insert a fiber mesh when applying the first coat of MICROSUPER7 and then MICROPRIMER ATTAC.

Before use, read carefully MICROLOGGIA 5F technical data sheet.

Application Methods



Stainless steel stick and trowel: Dissolve 1 kg of powder in 0.4 liters of water slowly adding the powder to avoid the formation of lumps. Apply directly the product thus obtained. Proceed with two or more skims at about 6 hours apart until all unevenness between the tiles is eliminated. The data shown in the table refer to an application at the temperature of 20 °C and a relative humidity rate not exceeding 50%.

Application temperature:	+5 +40	°C
Relative humidity of application:	< 50%	
Recommended thickness:	few millimeters	µm per coat
Sandable after:	6 - 8	h
Repaintable after:	24	h
Tools cleaning:	with water	h

Specific weight:	1,75 ÷ 1,85 (diluted)	Kg/l
Viscosity:		cPs
pH:	7 – 8	
Solid in weight:	72% once diluted	
Theoretical yield for 2 coats:	1	mq/l
Color:	white	
Appearance:	mat	
Packaging:	5 -15	kg

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.