

# STUCCO P3D ALTO SPESSORE IN POLVERE

## SCHEDA TECNICA

Revisione : 20/02/2023

Prodotto: **Stucco p3d alto spessore in polvere**

Categoria: Plasma 3D

Azienda: Example

### General Characteristics

Powder putty based on specific resins and mixtures of selected charges and fillers which give hardness and prevent the carbonation effect. Excellent adherence and workability. Excellent thixotropy which avoids sagging. Ease of application. High resistance and excellent sandability

### Application

Filler used to mask the joints of tile floors, porcelain stoneware, etc. for internal and external use and obtain a smooth surface for the 3D PLASMA cycle.

### Preparation of the surface



Make sure the surface is perfectly dry. If necessary, remove the dirt from the joints by passing the blade of a steel stick and eliminate any residue thus produced. Eliminate any presence of grease with suitable washing solvents.



### Application Methods



Stainless steel stick and trowel: Dissolve 1 kg of powder in 0.4 liters of water slowly adding the powder to avoid the formation of lumps. Apply the product thus obtained. Proceed with two or more browses about 6 hours apart until all unevenness between the tiles is eliminated. The data shown in the table refer to an application temperature of 20 °C and a relative humidity rate not exceeding 50%.

Application temperature:	+5 +40	°C
Relative humidity of application:	< 50%	
Recommended thickness:	few millimeters	µm per coat
Sand after:	6 - 8	h
Repaintable after:	24	h
Tool cleaning:	water	

Specific weight:	1,75 ÷ 1,85 (diluted)	Kg/l
Viscosity:		cPs
pH:	7 – 8	
Solid in weight:	72% once diluted	
Theoretical yield:	2	mq/kg
Color:	white	
Appearance:	mat	
Packaging:	1 - 5 -15	kg

## Storage:

---



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## Safety Precautions:

---

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## Warnings

---

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**