

MICROVETRO 1K OPACO

SCHEDA TECNICA

Revisione : 02/10/2024

Prodotto: **Microvetro 1k Opaco**

Categoria: Plasma 3D

Azienda: Loggia

General Characteristics

The product is formulated with water-based acrylic resins; it is odorless, non-yellowing and resistant to atmospheric agents. It is used as protection with a "vitrifying effect" for wall surfaces on which are applied decorative effects with both an organic and mineral nature. It is available in glossy and satin versions

Application

Suitable for obtaining a "vitrifying" effect as well as protecting opaque surfaces. Applied on walls or on wooden objects, where you want to make it impervious to dirt and water. Protects surfaces (concrete, stone, etc.) against damage caused by CO₂ carbonation and the aggressive action of sulfur dioxide (SO₂), guaranteeing at the same time excellent water repellency and reasonable vapor permeability. It resists adverse climatic conditions, the aggression of smog, salt and sunlight

Preparation



Thoroughly clean the surface to be treated and make sure it is dry before proceeding with the application of the product. It is crucial to apply MICROVETRO 1K when the decorative surface is perfectly dry (at least 3 days after having applied it) to minimize the formation of air bubbles.

Application Methods



Roller for clear and brush: the product is ready to use. Spread it evenly with the roller or brush in a single coat. Wait 12 hours before applying a second coat.

Application temperature:	+15 ÷ +30	°C
Relative humidity of application:	< 85%	
Dust dry:	4 ÷ 6	h
Repaintable after:	12	h
Deep dry:	7	h
Tools cleaning:	water	
Specific weight:	1,1	Kg/l
Solid in weight:	47%	
Theoretical yield:	10	mq/l
Color:	Transparent	
Appearance:	Glossy or mat	
Packing:	0,750 - 4	l

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.