

# MARMO LIQUIDO

## SCHEDA TECNICA

Revisione : 02/05/2024

Prodotto: **Marmo liquido**  
Categoria: Linea Impero  
Azienda: Loggia

### General Characteristics

Decorative spatula coating for interiors, formulated with synthetic binders, thickeners, calcium carbonates and special additives. This formula combination ensures a semi-gloss effect, resistance to dirt and protection.

### Use

Semi-gloss effect finish to be applied on Marmo Romano decorative. MARMO LIQUIDO gives different nuances and ensure protection to the decorative. Suitable for the internal finishing of artistically interesting ancient or modern buildings, precisely because of its elegance and refinement.

### Media Preparation



Before the application it is necessary to prepare the surface using powder or paste grouts (such as FLYSTUK), subsequently smoothed with abrasive paper (a grit type P120 is recommended) approximately 12 hours after the end of application. After sanding, proceed with the elimination of dirt and dust, apply a coat of FISSACRIL acrylic fixative diluted with water in the ratio 1:1 / 1:3. 4-5 hours after applying the fixative, apply 1 coat of Primer for Marmo Romano using a roller to unify the various absorptions of the wall. Stainless steel spatulas or trowel: Ready to use. If necessary, for special needs, add max 5% of water.



Apply a coat of Marmo Romano with a stainless steel trowel with a thickness of about 1.5: 2 mm while the product is still damp. Work MARMO ROMANO with the special Hellenica pad, to recreate the characteristic irregular veining of the marble. (For more information, see the Roman Marble technical data sheet).

### Application Methods



Stainless steel spatulas or trowel: Ready to use. If necessary, for special needs, add max water. When MARMO ROMANO is completely dry apply 1 or 2 coats of Marmo Liquido with a stainless steel trowel.

Application temperature:	5 - 35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	0,5 ÷ 1	µm per coat
Dust dry:	2-4	h
Repaintable after:	8	h
Deep dry:	24	h
Tool cleaning:	WATER	

## **Technical Characteristics**

Specific weight:	1.6	Kg/l
Viscosity:	30000-35000	cPs
pH:	12-13	
Solid in weight:	72%	
Theoretical yield:	7-8	m <sup>2</sup> /kg
Packs:	1, 2.5, 5	kg
Color:	Color folder	
Appearance:	semi-gloss	

## **Storage:**



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## **Safety Precautions:**

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## **Specification items:**

Glossy spatula decorative coating. Prepare the substrate with one coat of FISSACRIL sealer and two coats of Primer Acrilico. Application of two coats of Marmo Liquido in the required quantity to obtain a suitable dry film thickness. Everything must be done in compliance with the application rules, with a cost of € ..... per square meter including material and installation.

## **Warnings**

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –  
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**