




LOGGIA
industria vernici

TECHNICAL DATA SHEET

Issue Date: 7 novembre 2014



Fashion

Chromatic changing decorative coating with damask effect.

General Characteristics

Typology of the product: Fashion is a decorative coating with a pearlescent effect which recalls precious silver and gold damask tissues. The irregular and slightly embossed drawings together with the fantasy of the silver and golden shades give an atmosphere antique and precious.

Recommended Usage: It is recommended for the interior decoration of walls, columns... of high prestige classical building.

Preparation

Surface Preparation:

Clean carefully the surface that must be decorated (walls or plasterboards) removing dirty and impurities using sandpaper. Prepare the surface with powder or paste putty such as Flystuk to provide a smooth surface, then proceed to light sanding after 12 hours with abrasive paper P120-P150. Dab one coat of fixative FISSACRIL (dilute 1:1 - 1:3 with water) followed, after 4-5 hours, by one or two coats of white or brown UNIVERSAL PRIMER by using a roll.



Product Application

Methods:

Brush and trowel or plastic spatula: Ready to use.



Wait 6-8 hours since the application of the Primer then spread a coat of FASHION and cross the brush strokes irregularly. Distribute the product all over the surface squeezing the flocks with irregular movements and a slight pression of the spatula every 4 – 5 m². Wait 4-6 hours until the squashed flocks come down into the film to produce the desired damask effect. Apply one coat of VETRIFICANTE 1K P3D WALL diluted at 10% with water giving to the cover qualities of protection and washability.

Temperature of application:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Dry film thickness:	1 ÷ 2	mm
Touch dry:	1 ÷ 2	h
Repaintable after:	6 - 8	h
Completely dried:	24	h
Cleaning tools:	by water	

Colouring



This product can be colored with the Tinting Systems L'ANGELO and L'ANGELO OX.

Care should be taken when one uses different batches of the same colour. Mix them together to ensure color uniformity during application.

Hand mixing product by the appropriate spat is recommended to avoid the flocks breakage.

Technical properties

Density:	0,95 ÷ 1,10	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight Solids:	50%	
Coverage:	5 – 6	mq/l
Colour:	Color cards	
Feature:	Embossed gold and silver	
Pack Size:	0,75 - 4 – 14	l

Storage



Shelf-life: 2 years in original tightly closed containers away from direct sunlight and excessive heat.

The can should be resealed and stored tightly closed to prevent evaporation of the product and entry of air. Store it upside down after use.



Min storage temperature: +5°C (41°F)

Max storage temperature: +30°C (86°F)

Safety Precautions

Refer to the Material Safety Data Sheet before use.

Item specifications

Chromatic changing decorative coating with damask effect. Preparation of the surface with a coat of fixatif FISSACRIL and one or two coats of Universal Primer. Spreading of one coat of FASHION according to the information provided above with a cost of € at mq material and pose in work included..

General Information

Every care is taken to ensure that the information provided in this technical data sheet is accurate. **Loggia Industria Vernici S.r.l.** takes no responsibility for the results obtained through the use of this product in as much as it is not possible for **Loggia Industria Vernici S.r.l.** to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.