

EFFETTO TAMPONATO SILOSSANICO

SCHEDA TECNICA

Revisione : 25/09/2023

Prodotto: **Effetto tamponato silossanico**

Categoria: Linea Impero

Azienda: Loggia

General Characteristics

Decorative glaze based on siloxane resins with a high degree of vapor permeability and water repellency.

Application

The product is used in decorative finishes for interiors and protection and decorations of external facades. It can be applied on washable paints, on quartz paints, lime and silicate paints, or on siloxane paints. Suitable for decorating and protecting plaster.

Preparation of the surface



Before applying the product make sure that the paint to be decorated is perfectly dry. If necessary, clean the wall with a cloth removing accumulated dust and dirt particles.

Application Methods



Paintbrush, Decorative Glove or cloth: Dilute the product to a maximum of 5% with water.

Proceed with the application of the effect by crossing the brush strokes one over the other until the surface is completed, thus obtaining an antiqued, breathable and water-repellent decoration.

Warnings: Do not apply on surfaces exposed to the sun.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	20 ÷ 35	µm per coat
Dust dry:	4 ÷ 6	h
Repaintable after:	12	h
Deep dry:	24	h
Tool cleaning:	water	

Painting:



The product can be colored with the tintometric systems L'ANGELO and L'ANGELO OX lines, as well as with the universal dyes found on the market.

It is advisable to mix different manufacturing batches of the same color together to avoid possible differences in shade during application.

Specific weight:	0,9 ÷ 1,0	Kg/l
Viscosity:		cPs
pH:	7-8	
Solid in weight:	10%	
Theoretical yield:	7 – 8	mq/l
Color:	Folder Colors	
Appearance:	Translucent opaque	
Packing:	0,75 - 4 – 14	

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.