




**LOGGIA**  
industria vernici

# TECHNICAL DATA SHEET

Revisione: 11 novembre 2014



## *Domus Aurea, Domus Diamante Argento/Oro, Domus Oro and Domus Argento.*

Decorative thick coating antique look.

### General Characteristics

---

<b>Composition:</b>	Decorative coating of high quality with thick, irregular, veiled shades which give the rooms a precious and ancient look. Suitable for the protection and decoration of villas and apartments, hotels, shops ... where you want to obtain a warm and antique effect. The product is washable, water-repellent, transpiring and prevents the formation of mold
<b>Recommended usage:</b>	Suitable for indoor use, such as walls, columns and interior walls pretreated with quartz finish.

### Application

---



<b>Surface preparation:</b>	Before applying the effect Domus Aurea proceed to a proper preparation of the surface by means of fillers in powder or paste (type FLYSTUK), then smooth with abrasive paper (we recommend a grain type P120) after about 12 hours of the end application. After sanding eliminate dirt and dust and apply a coat of vinyl FISSAMUR diluted with water in the ratio 1: 1/1: 3. After 4-5 hours from the application of the fixative apply, by means of a roller, 2 coats of Primer MAXI FOND spaced by about 5-6 hours apart. The primer should be white or the same color tone you chose for the Domus Aurea, but with a lower degree of intensity.
-----------------------------	--



### Application techniques

---

<b>Application methods:</b>	<i>Spalter or Plastic spatula</i> : ready to use.
-----------------------------	---



6-8 hours after the application of the primer, apply Domus Aurea by crossing movements of the decor tool in a uniform manner until completion of the wall. Every 3-4 minutes pass the spatula (type Loggia) with a light pression, so squeezing the flake until you get the desired effect. From 4 to 6 hours, the flake will fall flat in the film giving, very simply, a wonderful decoration in your home or office.

Temperature of application:	+5 ÷ +35	°C
Humidity for application:	< 85%	
Recommended thickness:	80 ÷ 120	µm
Touch dry:	4 ÷ 6	h
Recoatable after:	12	h
Completely cured after:	24	h
Tools cleaning:	with water	

## Colouring



The product could be colored with Tinting System L'ANGELO and L'ANGELO OX, as well Universal toners that can be found on the market. It is recommended to mix different batches to avoid possible differences of shades during the application.

## Technical properties

Density:	0,95 ÷ 1,05	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight solids:	50%	
Coverage:	5 – 6	mq/l
Color:	Colori di Cartella	
Aspect:	rustic antique, thick	
Pack size:	0,75 - 4 – 14	l

## Storage



Shelf-life: not less than 2 years original tightly closed. Store away from direct sun and excessive heat.

The can should be resealed and stored tightly closed. Store it upside down after use.



Min storage temperature: +5°C

Max storage temperature: +5°C

## Safety Precautions

**For all information regarding product use and correct product disposal please refer to Safety Data Sheet.**

## Specifications items

**Decorative thick coating antique look.** Surface preparation with 1 coat of FISSAMUR and 2 of Primer MAXI FOND. Application of 1 coat of DOMUS AUREA according to the quantity absorbed by the surface in order to obtain a suitable dry film thickness. All must be made in accordance with the implementing rules, with a cost of € ..... for m2 including material and pose in work.

## Warnings

All information contained in this data sheet are based on our technical knowledge. However these indication could not have a value of guarantee for applicator considering that conditions of applying of product are out of our control. It is advisable make sure of suitability of the product making previous test.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.**