




LOGGIA
industria vernici

TECHNICAL DATA SHEET

Revisione: 7 novembre 2014



Effetto Jeans

Textured decorative refinishing


General Characteristics

Composition: Effetto Jeans is acrylic decorative finishing for modern environments with metallic and slightly rough on touch. Final result is striated as a Jeans.

Recommended Usage: The product is indicated for decoration of interior walls and plasters already painted with acrylic paint on.

Application

Surface preparation:



Before to apply Effetto Jeans is necessary to prepare surface with powder or pasty putty (as Flystuk) and shave it after about 12 hours with sanding paper (recommended grain type P120). After sanding clean well surface removing dirtiness and dust, apply one coat of acrylic fixative FISSACRIL tinned 1:1/1:4 with water. After 4-5 hours of fixative application proceed applying 2 coats of UNIVERSAL PRIMER by roller or brush, 5-6 hours one from another. The Primer should be white or in the same color of Jeans but one shade lighter.

Product Application

Application Methods: *By roller or brush: Tin it with water at 5%*



About 12 hours after primer application proceed with application of first coat of Jeans with short hair roller, brushing it immediately by brush horizontally. After 4-6 hours apply the second coat in the same way but brushing it vertically. Final result should be effect of Jeans texture.

Temperature for application:	+5 ÷ +35	°C
Humidity for application:	< 85%	
Recommended thickness:	35 ÷ 50	µm per coat
Touch dry:	4 ÷ 6	h
Recoatable after:	4 - 6	h
Completely cured:	24	h
Tools cleaning:	with water	

Colouring




This product can be coloured with the Tinting Systems L'ANGELO and L'ANGELO 4OX.

Care should be taken when one uses different batches of the same colour. Mix them together to ensure colour uniformity during application.

Technical Properties

Density:	0,95 ÷ 1,05	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight Solids:	25%	
Coverage:	8 – 9	mq/l
Colour:	Color chart	
Gloss level:	rough as Jeans	
Pack size:	0,75 - 4 – 14	l

Storage



Shelf-life: 2 years in original tightly closed containers away from direct sunlight and excessive heat. The can should be resealed and stored tightly closed to prevent evaporation of the product and entry of air. Store it upside down after use.

Min storage temperature: +5°C

Max storage temperature: +30°C

Safety Precautions

Refer to the Material Safety Data Sheet before use.

General Information

Every care is taken to ensure that the information provided in this technical data sheet is accurate. **Loggia Industria Vernici S.r.l.** takes no responsibility for the results obtained through the use of this product in as much as it is not possible for **Loggia Industria Vernici S.r.l.** to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

Azienda certificata BVQI per il sistema di qualità UNI EN ISO 9001-2000.