

DOROTEA GOLD GRANA FINE

SCHEDA TECNICA

Revisione : 07/03/2024

Prodotto: **Dorotea Gold grana fine**

Categoria: Linea Impero

Azienda: Loggia

General Characteristics

Interior covering of great charm with metallic, silvery or golden effect reflections, with fine or coarse grain.

Application

Due to its elegance, Dorotea is ideal for the protection and decoration of internal walls of prestigious ancient or modern buildings, such as villas, hotels, banks and offices.

Surface Preparation



Thoroughly clean the surfaces (walls or plasterboard) that need to be decorated, carefully removing all impurities using abrasive paper. Prepare the surface with powder or paste fillers (such as Flystuk). 12 hours after finishing applying the smoothing putty, sand with P120-P150 type abrasive paper. Apply a coat of FISSAMUR vinyl fixative diluted 1:3 with water. Wait 4-5 hours and apply 1-2 coats of Primer MAXI FOND.



Application Methods



Brush or Plafoncino or Glove for decorations: Ready to use. If necessary, add 5% water. After 6-8 hours have passed since the end of the application of the MAXI FOND, proceed with the application of a first coat of Dorotea using a decor glove or with a plafond, crossing the brushstrokes in an irregular manner until the wall is completed. After 4-6 hours, apply a second hand following the same instructions as for the first until the desired effect is obtained.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	35 ÷ 50	µm per coat
Dust dry:	4 ÷ 6	h
Repaintable after:	12	h
Deep dry:	24	h
Tool cleaning:	water	

Painting:



The product can be colored with the tintometric systems of the L'ANGELO, L'ANGELO OX and MAXXI lines, as well as with the universal dyes found on the market. It is advisable to mix different manufacturing batches of the same color together to avoid possible differences in shade during application.

Specific weight:	1,1 ÷ 1,2	Kg/l
Viscosity:	13000 - 15000	cPs
pH:	8 - 9	
Solid in weight:	40%	
Theoretical yield:	7 – 8 mq/l Infinito e Marmo Romano; 6-7 mq/l Maxifond	mq/l
Recommended coats of paint:	2	
Color:	Folder Colors	
Appearance:	Semi-gloss waxed	

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.