

UNIVERSAL PRIMER

SCHEDA TECNICA

Revisione : 04/10/2022

Prodotto: **Universal Primer**

Categoria: Fondi

Azienda: Loggia

General Characteristics

Wall water-based paint formulatd with special acrylic copolymers, pigments and selected fillers. Excellent coverage and yield. Opaque in appearance.

Application

Used as a colored basecoat on walls before applying PLASMA 3D and other decorative such as:

Vanesia, Vanesia Glitter Oro, Vanesia Glitter Argento, Vanesia Oro, Velluto Fiorentino, Velluto Fiorentino Glitter oro, Velluto Fiorentino Glitter Argento, Velluto Fiorentino Oro, Seta d'Autore, Seta d'Autore Glitter oro, Seta d'Autore Glitter Argento, Seta d'Autore Oro, Stucco Antico, Kymera, Diamond Oro, Diamond Argento, Fashion, Perlato, Perlato Oro, Maxipearl, Effetto Cerato, Luminor Oro, Luminor Argento, Effetto Jeans, Sharki, Sharki Gold, Sharki Silver, Sharki Silver Diamante, Sharki Gold Diamante Glitter Oro, Sharki Gold Diamante Glitter Argento, Oro Puro, Oro Diamante, Replay, Domus Aurea, Domus Diamante Oro, Domus Diamante Argento, Domus Oro, Domus Argento, Domus Noir.

Preparation



Check that 4-5 hours have passed since the application of PRIME P3D WALL and that the surface is perfectly clean. Apply the product as described below.

Application Methods



Brush and Roller: Dilute with a maximum of 10-15% of water for application with the roller and 20% for application with a brush, both for the first and second coat. Wait 5-6 hours between one application and the next.

Application temperature:		°C
Relative humidity of application:		
Recommended thickness:		µm per coat
Dust dry:		h
Repaintable after:		h
Deep dry:		h
Tool cleaning:		

Painting:



The product can be colored with the tinting system of the L'ANGELO 4OX line.

It is advisable to mix different manufacturing batches of the same color with each other to avoid possible differences in shades during application.

Specific weight:	1,2 ÷ 1,3	Kg/l
Viscosity:	8.000 ÷ 10.000	cPs
pH:	7-8	
Solid in weight:	58%	
Theoretical yield:	12-14	mq/l
Packaging:	0,75 - 4	
Color:	Folder 4OX	
Appearance:	matt	

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.