




**LOGGIA**  
industria vernici

# TECHNICAL DATA SHEET

Issue Date: 15 gennaio 2014



## Intermedial P3D Floor

Acrylic colorable matt primer for floor and tiles.

### General Characteristics

---

**Composition:** Water-based paint consisting of special acrylic copolymers, pigments and selected charges. Excellent coverage and yield. Of matt appearance.

**Recommended Usage:** Used as a colored primer on floors and tiles before applying PLASMA 3D.

### Preparation

---


**Surface Preparation:** Verify that have passed at least 12 hours from the application of the VETRIFICANTE EPOSSIDICO BICLEAR 2K H<sub>2</sub>O and that the surface is perfectly clean. Apply the product as described below.



### Product Application

---

**Methods:**



*Roller:* Dilute to max 5% of water both for the first and for the second coat. Wait 5-6 hours between one application and the next.

Temperature of application:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	35 ÷ 50	µm for coat
Touch dry:	0,5	h
Overpaint after:	5 ÷ 6	h
Complete curing:	24	h
Cleaning tools:	with water	

## Colouring

---



This product can be coloured with the Tinting Systems L'ANGELO 40X.

Care should be taken when one uses different batches of the same colour. Mix them together to ensure colour uniformity during application.

## Technical properties

---

Density:	1,3 ÷ 1,4	Kg/l
Viscosity:	8.000 ÷ 10.000	cPs
pH:	7-8	
Weight Solids:	58%	
Coverage:	8 – 10	mq/l for coat
Colour:	Color cards 40X	
Feature:	matt	
Pack Size:	0,75 - 4	l

## Storage

---



Shelf-life: 2 years in original tightly closed containers away from direct sunlight and excessive heat.

The can should be resealed and stored tightly closed to prevent evaporation of the product and entry of air. Store it upside down after use.



Min storage temperature: +5°C (41°F)

Max storage temperature: +30°C (86°F)

## Safety Precautions

---

**Refer to the Material Safety Data Sheet before use.**

## General Information

---

Every care is taken to ensure that the information provided in this technical data sheet is accurate. **Loggia Industria Vernici S.r.l.** takes no responsibility for the results obtained through the use of this product in as much as it is not possible for **Loggia Industria Vernici S.r.l.** to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.**