

# SOFFIO PIÙ

## SCHEDA TECNICA

Revisione : 04/02/2022

Prodotto: **Soffio Più**

Categoria: Idropitture per Interni

Azienda: Loggia

## General Characteristics

Breathable covering paint for interiors based on vinyl copolymers and selected high-resistance fillers. Additive with broad spectrum bactericide and with a pleasant pine scent. Easy to apply.

## Application

Suitable for painting ceilings, bathrooms, kitchens, interior walls. Applicable on plasters based on hydraulic binders, gypsum or plasterboard and absorbent conglomerates of various kinds, both new and old, as long as they are not chalking.

## Media Preparation



**New Internal Surfaces:** Make sure that the substrate is perfectly dry and cured - not less than 4 weeks for civil plasters and 2 weeks for premixed plasters. If necessary, fill any holes or imperfections with FLYSTUK and sand; finally clean the surfaces. Then apply a coat of FISSAMUR insulator and after 4-6 hours paint with two coats of SOFFIO PIU' following the technical instructions below.



**Internal Painted Surfaces:** Eliminate any traces of mold by brushing off the efflorescence after treating them with acid. Then sanitize with a coat of MUFFACID. Remove flaking residues of old paint and, if necessary, fill and smooth imperfections with FLYSTUK; sand and clean the surfaces. Then apply a coat of FISSAMUR insulator and after 4-6 hours paint with two coats of SOFFIO PIU' following the technical instructions below.



## Application Methods



**Brush:** Dilute 20-30% with water for both the first and second coat. Wait 4-5 hours between one application and the next.



**Roller:** Dilute 20% with water for both the first and second coat. Wait 4-5 hours between one application and the next.

**Airless:** In airless applications the dilution varies depending on the equipment and pressure used.



Application temperature:	+5 ÷ +35 °C	°C
Relative humidity of application:	< 85%	
Recommended thickness:	35 ÷ 40	µm per coat
Dust dry:	30 minutes	
Repaintable after:	4-5	h
Deep dry:	24	h
Tool cleaning:	by water	

## Painting:



The product can be colored with universal dyes available on the market, but only pastel shades are recommended.

It is advisable to mix different manufacturing batches of the same color with each other to avoid possible differences in shades during application.

Specific weight:	1.65 ÷ 1.70	Kg/l
Viscosity:	18000 ÷ 22000	cPs
pH:	7-8	
Solid in weight:	68%	
Theoretical yield:	8-10	mq/l
Package:	2.5 - 5 – 14	
Color:	White	
Appearance:	Matt	

## Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

## Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

## Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and

suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**BVQI certified company for the UNI EN ISO 9001-2000 quality system.**