

ITALIAN GRAFFITI SOLV

SCHEDA TECNICA

Revisione : 24/04/2026

Prodotto: **Italian Graffiti SOLV**

Categoria: Antigraffiti

Azienda: Loggia

General Characteristics

A two-component, non-yellowing polyurethane clearcoat formulated with a highly hydroxyl-functional, branched saturated polyester catalyzed by an aliphatic isocyanate (component B). It contains special silicone additives that provide permanent slipperiness, preventing the adhesion of other paints without compromising its strong adhesion to the substrates being protected. It is scratch- and pollutant-resistant and can be washed out even with strong solvents, allowing the removal of graffiti from permanent markers, spray paints, etc.

Application

Ideal for protecting surfaces such as marble, travertine, exposed brick, pietra serena, cortina, natural stone in general, and metal surfaces. It can also be applied to cured plastic coatings, subject to a peel test. The final result will be a glossy finish.

Warnings: To remove graffiti, you can use either nitro thinner or the specific TOGLIGRAFFITI SOLV-GEL. The product is tested to withstand 10 wash cycles with nitro thinner without undergoing significant changes.

Surface Preparation



Exterior Surfaces: Make sure the surface is completely dry. Remove any dirt or flaking paint. Thoroughly clean the surfaces to be treated. Then apply a coat of ITALIAN GRAFFITI following the technical instructions below.



Application Methods



Catalysis

Mix the product 2:1 by volume with PU 1000 catalyst for ITALIAN GRAFFITI SOLV.

Brush, Roller, and Spray: Dilute the mixture if necessary with 5% polyurethane thinner. Apply an even coat of product to the surface.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	20 ÷ 25	µm per coat
Dust dry:	2	h
Repaintable after:	12	h
Deep dry:	24	h
Tool cleaning:	with nitro thinner	

Specific weight:	0,90 – 1,05	Kg/l
Solid in weight:	40%	
Theoretical yield:	8 – 10	mq/l
Packaging:	0.5 - 1 –5 – 20	l
Color:	Colorless	
Appearance:	Transparent	

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.