

VERNIROAD-RIFRA

SCHEDA TECNICA

Revisione : 20/01/2025

Prodotto: **Verniroad-rifra**
Categoria: Linea Industria
Azienda: Loggia

General Characteristics

Paint for road markings based on modified alkyd resins and light-resistant pigments, with reflective glass beads. It is characterized by rapid drying, good adhesion and elasticity and excellent wear resistance. Resistant to mechanical action due to trampling and transit of vehicles.

Application

Specific product for road signs suitable for any type of surface: road asphalt, concrete, industrial flooring, etc. Classification (UNI 8681) B4. A.O.B.2.BD Paint for finishing coat, in solution, single-component, with oxidative chemical hardening, matt, chloroalkyd.

Media Preparation



Surfaces to be Treated: apply on the surface perfectly dry and free from traces of grease and oil otherwise, remove any kind of trace with sawdust, sand or something else. Carefully clean the road surface by sweeping away the coarsest dust before applying VERNIROAD Rifra following the technical instructions below.



Application Methods



Brush and Roller: Dilute as required with traffic thinner.

Line marking machine: Dilute with 5 -10% traffic thinner.

Air spray: Dilute 15-20% with traffic thinner. Nozzle 2.5 – 3 mm, pressure 4 Atm. It can be applied in just one hand.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	100	µm per coat
Dust dry:	20	h
Repaintable after:	30 ÷ 45	h
Tool cleaning:	with nitro thinner	

Painting:



Testo da inserire

Specific weight:	1,6 ÷ 1,7	Kg/l
Viscosity:	70 - 80	cPs
Solid in weight:	79%	
Theoretical yield:	5 - 7	m ² /l
<i>Recommended coats of paint:</i>	<i>5 - 30</i>	
Color:	White, yellow, blue, black	
Appearance:	Matt	

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months.



After use carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.